

COMMERCIAL RANGE

533mm, 610mm

UNIVENT Technical Specifications and Performance

UNIVENT	533mm	610mm
Throat Size	533mm	610mm
Number of Blades	36	
Steel Bearings	2	
Nylon Dust Shields	3	
Shaft	10mm (stainless steel)	
Inner Arm	1.2mm	
Square to round base (Up to 18 degrees)	Available	
Variable Pitch Base (Up to 45 degrees)	Available	
Exhaust capacity (litres per second)	575	1141
Cyclone Tested	Yes	No
Approximate weight (rotor head only)	3kg	3.8kg
Box Dimension	62cm x 62cm x 38cm	70cm x 70cm x 40cm

Powder coating to colorbond colors optional and available on request. (additional charges apply) Standard Mill finish

Product Features

All aluminium, anti-corrosive construction (Australian Grade 5005 H34)

Dual heavy duty bearings (10mm)

Stainless steel shaft and supporting arms

Nylon dust shields to protect bearings from dust and foreign particles

10 years product manufacturers warranty

Available with variable pitch base or customised zincanneal base







POWDER COATINGResidential & Commercial

Powder coating is available for all sized roof ventilators.

Our smallest sizes, the 300mm and 360mm sized vents are all kept in stock in Colorbond colours. However our larger sizes, the 410mm, 530mm and 610mm are only powder-coated on request. Below are the Colorbond colours our vents are available in.

We also stock and will still powder coat superseded colours such as: **Bushland, Headland, Plantation, Sandbank, Wilderness and Loft.**

